

Tyrone Camarero Specifications

Tyrone

Camarero DA400T3R-424R

Key features

- Dual AMD Opteron™ 4000 series (4300 ready) processors (Socket C32) 8/6/4-Core ready; HT3.0 Link support
- AMD SR5690 + SP5100 Chipset
- Up to 256GB DDR3 1600MHz ECC Registered DIMM; 8x DIMM sockets
- 24 x 3.5" Hot Swap SAS Drives Bays
- 6x SATA (3.0 Gb/s) ports via AMD SP5100 controller, RAID 0, 1, 10
- 1 PCI-E 2.0 x8 (in x16 slot) ,3 PCI-E 2.0 x8 , 1 PCI-E 2.0 x4 (in x8 slot) 1 PCI
- Integrated Matrox G200eW Graphics
- 6x SATA (3.0 Gb/s) ports via AMD SP5100 controller, RAID 0, 1, 10
- 920W Redundant Power Supplies Platinum Level (94%)



Processor/Cache		Front Panel :	
Processor	Dual AMD Opteron™ 4000 series (4300 ready) processors (Socket C32) 8/6/4-Core ready; HT3.0 Link support	LEDs	Power LED,Hard drive activity LED,2x Network activity LEDs,System Overheat LED,Power Fail LED
		Buttons	Power On/Off button,System Reset button
System Memory		Drive bays	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Supports up to 256 GB DDR3 ECC Registered memory	HDD bays	24 x 3.5" Hot Swap SAS Drives Bays
		Peripheral Bays :	None
Expansion Slots		Power Supply	
PCI-Express	1 PCI-E 2.0 x8 (in x16 slot) ,3 PCI-E 2.0 x8 , 1 PCI-E 2.0 x4 (in x8 slot) 1 PCI	920W Redundant Power Supplies Platinum Level (94%)	
Integrated On-Board		Cooling System	
SATA	AMD SP5100 (RAID 0, 1, 10)	3x 80mm Hot-swap 4-pin PWM Fans 2x 80mm Rear-exhaust 4-pin PWM Fans	
LAN	2 RJ45 LAN ports, 1 RJ45 Dedicated LAN supports IPMI		
Add-on Options		Form Factor	
RAID card optional		4U Storage Chassis with Expender for Scalability	
Optical Drive : None		Height 7" (178mm), Width 17.2" (437mm) Depth 26" (660mm)	
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	