

Tyrone Camarero Specifications



Camarero DA400T3T-14

Key features

- Dual AMD Opteron™ 4000 series (4300 ready) processors (Socket C32) 8/6/4-Core ready; HT3.0 Link support
- Up to 192GB DDR3 1600MHz ECC Registered DIMM; 12x DIMM sockets
- 920W High-efficiency Power Supply Platinum Certified
- 1 Low Profile PCI-E Gen2.0 x16 expansion slot
- 2x Hot-swappable SATA Hard Drive Bays
- 1 dedicated LAN for system management (IPMI2.0)



Processor/Cache	
Processor	Dual AMD Opteron™ 4000 series (4300 ready) processors (Socket C32) 8/6/4-Core ready; HT3.0 Link support
System Memory	
Memory Capacity	12 DIMM sockets Support up to 192GB Registered ECC or 64GB Unbuffered ECC
Expansion Slots	
PCI-Express	1 Low Profile PCI-E Gen2.0 x16 expansion slot
Integrated On-Board	
SATA	AMD SP5100 (RAID 0, 1)
LAN	2 RJ45 LAN ports 1 RJ45 Dedicated LAN supports IPMI
Add-on Options	
RAID card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED
Switches	Power On/Off Button, System Reset Button
Drive bays	
HDD bays	2 x 3.5" SATA hard drive bays
Peripheral Bays	None
Power Supply	
920W High-efficiency Power Supply 80Plus Platinum Certified	
Cooling System	
6x counter-rotating PWM fans w/ Optimal Fan Speed Control	
Form Factor	
1U Rack mount	
Height	1.7" (43mm),
Width	17.2" (437mm)
Depth	27.75" (705mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	