

Tyrone Camarero Specifications



Camarero DA600T3G-13

Key features

- 2x double width GPU cards supported, optimized for GPU solution
- Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready; HT3.0 Link support
- Up to 512GB DDR3 Registered ECC 1600/1333/1066 SDRAM in 16 DIMMs
- 2x full height full length PCI-e Gen 2.0 x16 slots; 1x low-profile PCI-e x8 Gen 2.0 in x16 slot
- Dual-port GbE LAN Controller, 4xUSB 2.0 ports, 1x dedicated LAN for system management
- 3x Hot-swap SATA Drive Bays
- 1400W High-efficiency Power Supply 80Plus Gold Certified
- 1x Low-profile PCI-E 2.0 in x16 slot



Processor/Cache

Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready; HT3.0 Link support

System Memory

Up to 512GB DDR3 Registered ECC 1600/1333/1066 SDRAM in 16 DIMMs

Expansion Slots

2x full height full length PCI-e Gen 2.0 x16 slots;
1x low-profile PCI-e x8 Gen 2.0 in x16 slot

Integrated On-Board

AMD SP5100 (RAID 0, 1, 10)
LAN: 2 RJ45 LAN ports 1 RJ45 Dedicated LAN supports IPMI

Add-on Options

RAID card Optional
Optical Drive Optional

Front Panel :

LED Indicators: Power LED, Hard drive activity LED,
2x Network activity LEDs, Universal Information (UID) LED
Switches: Power On/Off Button, System Reset Button, UID Button

Drive bays

HDD bays : 3x 3.5" Hot-swap SATA drive bays
Peripheral Bays: Slim DVD-ROM drive (optional)

Power Supply

1400W High-efficiency Power Supply 80Plus Gold Certified

Cooling System

8x 4cm heavy-duty counter-rotating PWM fans with optimal fan speed control

Form Factor

1U Rack mount
Height 1.7" (43mm),
Width 17.2" (437mm),
Depth 28.2" (716mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com