Tyrone Camarero Specifications

Tyrone

Camarero DA600T3G-16

Key features

- 2x double-width full-heig ht/length GPU cards supported;
- Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready
- Up to 512GB DDR3 Registered E CC 1600/1333/1066 SD R AM in 16 DIMMs
- 2x full-height full-length PCI-e Gen 2.0 x16 slots; 1x low-profile PCI-e x8 Gen
 2.0 in x16 slot
- Dual-port GbE LAN Controller, 4xUSB 2.0 po rts, 1x dedic ated LAN for system management
- 6x 2.5" Ho t-swap S ATA Drive B ays
- 2x InfiniBand cards supported
- 1400W High-efficiency Power Supply 80Plus Gold Certified
- 1x Low-profile PCI-E 2.0 in x16 slot





Processor/Cache

Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready

System Memory

Sixteen DIMM sockets Support up to 512GB DDR3 1600/1333/1066 MHz memory

Expansion Slots

2x full-height full-length PCI-e Gen 2.0 x16 slots; 1x low-profile PCI-e x8 Gen 2.0 in x16 slot

Integrated On-Board

SATA AMD SP5100 (RAID 0, 1)
LAN:2 RJ45 LAN ports 1 RJ45 Dedicated LAN supports IPMI

Add-on Options

RAID card Optional Optical Drive : None

Front Panel:

LED Indicators: Power LED,Hard drive activity LED, 2x Network

activity LEDs, Universal Information (UID) LED

Switches: Power On/Off Button, System Reset Button, UID

Button

Drive bays

HDD bays : 6x 2.5" Hot-swap SATA drive bays HDD Bays

Peripheral Bays:None

Power Supply

1400W High-efficiency Power Supply 80Plus Gold Certified

Cooling System

8x 4cm heavy-duty counter-rotating PWM fans with optimal fan speed Control

Form Factor

1U Rack mount

Height 1.7" (43mm), Width 17.2" (437mm), Depth 28.2" (716mm)