

Tyrone Camarero Specifications

Tyrone[®]

Camarero DA600T3R-14R



Key features

- Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready; HT3.0 Link support
- Up to 512GB DDR3 Registered ECC 1600/1333/1066 SD RAM in 16 DIMMs
- 1x UIO and 1x PCI-e Gen 2.0 x16 slot
- Dual-port GbE LAN Controller, 4xUSB 2.0 ports, 1x dedicated LAN for system management (IPMI 2.0)
- 4x Hot-swap SAS/SATA Drive Bays
- 700W High-efficiency Redundant Power supplies, 80 Plus Gold Certified



<h3>Processor/Cache</h3>	<h3>Front Panel :</h3>
<p>Dual AMD Opteron™ 6000 series (6300P* ready) processors (Socket G34) 16/12/8/4-Core ready; HT3.0 Link support</p>	<p>LED Indicators: Power LED, Hard drive activity LED, 2x Network activity LEDs, Universal Information (UID) LED</p> <p>Switches: Power On/Off Button, System Reset Button, UID Button</p>
<h3>Chip Set</h3>	<h3>Drive bays</h3>
<p>SR5670 + SP5100</p>	<p>HDD bays : 4x Hot-swap SAS/SATA Drive Bays</p> <p>Peripheral Bays: Slim DVD-ROM drive</p>
<h3>System Memory</h3>	<h3>Power Supply</h3>
<p>Sixteen DIMM sockets Support up to 512GB DDR3 1600/1333/1066 MHz memory</p>	<p>700W High - efficiency Redundant Power Supplies; 80PLUS Gold Certified</p>
<h3>Expansion Slots</h3>	<h3>Cooling System</h3>
<p>1x UIO and 1x PCI-e Gen 2.0 x16 slot</p>	<p>4x 4cm Counter-rotating PWM fans</p>
<h3>Integrated On-Board</h3>	<h3>Form Factor</h3>
<p>SATA : AMD SP5100 (RAID 0, 1, 10)</p> <p>LAN: 2x RJ45 ports and 1x RJ45 Dedicated LAN support IPMI</p>	<p>1U Rack mount</p> <p>Height 1.7" (43mm), Width 17.2" (437mm), Depth 25.6" (650mm)</p>
<h3>Add-on Options</h3> <p>RAID card optional</p> <p>Optical Drive : Optional</p>	<p style="text-align: center;">Email : info@tyronesystems.com</p> <p style="text-align: center;">For more/current product information, visit www.tyronesystems.com</p>