

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

## Camarero DA700TN-48RT

### Key features

- **GPU Accelerated Compute, Cloud Computing, Data Center, General purpose, SMB, Web Hosting**
- Dual AMD EPYC™ 7000/7002 Series Processors ,Up to 32 Cores
- System on Chip (SoC)
- Up to 2TB Registered ECC DDR4 2666MHz SDRAM in 16 DIMMs
- 2 PCI-E x16 slots, 3 PCI-E x8 slots
- Integrated IPMI 2.0 + KVM with dedicated LAN
- Dual 10G LAN ports
- 8 hot-swap 3.5" SAS3/SATA3 drive bays; 2 peripheral 5.25" drive bays; 1 M.2 NVMe SSD supported
- 1280W Redundant Power Supplies Platinum Level



Processor/Cache	
Processor	Dual AMD EPYC™ 7000/7002 Series Processors ,Up to 32 Cores
Chipset	
Chipset	System on Chip (SoC)
System Memory	
Memory Capacity	16 DIMM sockets, Supports up to 2TB Registered ECC DDR4 2666MHz SDRAM in 16 DIMMs, 8-channel memory bus
Expansion Slots	
PCI-Express	2 PCI-E x16 slots, 3 PCI-E x8 slots
Integrated On-Board	
SATA	SATA3 (6 Gbps)
LAN	Dual 10G LAN ports, 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid	Optional
Optical Drive	Optional

Front Panel	
LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED / Fan fail LED /UID LED
Buttons	Power On/Off button, System Reset button
Drive Bays	
HDD bays	8 hot-swap 3.5" SAS3/SATA3 drive bays; 2 peripheral 5.25" drive bays; 1 M.2 NVMe SSD supported
Peripheral Bays	3 peripheral 5.25" drive bays
Power Supply	
1280W Redundant Power Supplies Platinum Level	
Cooling System	
3 internal hot-swap 9400 RPM fans, 2 external rear hot-swap 9400 RPM fans	
Form Factor	
Form Factor	Tower / 4U Rackmountable
Height	: 17.8" (452mm),
Width	: 7" (178mm),
Depth	: 25.5" (647mm)
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	