# **Tyrone Camarero Specifications**

# Tyrone

# Camarero DA7OOTR-212R4

#### **Key features**

High Performance Computing, AI / Deep Learning Supports up to 8 NVIDIA® HGX™ A100 GPUs; Highest GPU Communication using NVIDIA® NVLINK™ + NVIDIA® NVSwitch™; 8 NIC for GPU Direct RDMA (1:1 GPU Ratio) Supports HGX A100 8-GPU 40GB (HBM2) or 80GB (HBM2e) with NVLink/NVSwitch GPU interconnect and PCI-E Gen4 host CPUs

- Dual AMD EPYC<sup>™</sup> 7003/7002 Series Processors (7003 Series Processor drop-in support requires BIOS version 2.0 or newer) Socket SP3, Supports CPU TDP up to 280W, Up to 128 Cores (64 per CPU)
- System on Chip (SoC)
- 32 DIMM slots, Up to 8TB 3DS ECC DDR4-3200MH RDIMM/LRDIMM
- 8 PCI-E 4.0 x16 via PCI-E switch, 1 PCI-E 4.0 x16 LP and 1 PCI-E 4.0 x8 LP via CPUs
- 6 hot-swap U.2 NVMe 2.5"" drive bays (4 via PCI-E switch, 2 via CPU, SATA/NVMe Hybrid or SAS with optional HBA)
   (up to 10 hot-swap U.2 NVMe 2.5"" available)"
- Flexible Networking via AIOM, 1 dedicated IPMI LAN Port
- 4 Hot-swap heavy-duty cooling fans
- 2200W Redundant Power Supply / 3000W Redundant Power Supply







#### Processor/Cache

Processor

Dual AMD EPYC™ 7003/7002 Series Processors (7003 Series Processor drop-in support requires BIOS version 2.0 or newer) Socket SP3, Supports CPU TDP up to 280W, Up to 128 Cores (64 per CPU)

#### Chipset

Chipset

System on Chip

#### **System Memory**

Memory Capacity

32 DIMM slots, Up to 8TB 3DS ECC DDR4-3200MH RDIMM/LRDIMM

#### **Expansion Slots**

**PCI-Express** 

8 PCI-E 4.0 x16 via PCI-E switch,

1 PCI-E 4.0 x16 LP and 1 PCI-E 4.0 x8 LP via CPUs

# **Integrated Onboard**

SATA

4 SATA3 (6Gbps) ports

LAN

Provided by AIOM, 1 RJ45 Dedicated

IPMI LAN port

# **Add-on Options**

Raid Card:

Optional

Optical Drive:

None

## **Drive Bays**

6 hot-swap U.2 NVMe 2.5"" drive bays (4 via PCI-E switch, 2 via CPU, SATA/NVMe Hybrid or SAS with optional HBA) (up to 10 hot-swap U.2 NVMe 2.5"" available)"

## **Power Supply**

2200W Redundant Power Supply / 3000W Redundant Power Supply

# Cooling System

4 x Hot-swap 11.5K RPM heavy duty fans

#### **Form Factor**

Form Factor

**4U Rackmount** 

Dimensions

Height: 6.9" (174mm), Width: 17.6" (446mm),

Depth: 35.4" (900mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com

O AMD the AMD logo inside are trademarks of Advanced Micro Devices in US and / Or other Countries

O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners