

# Tyrone Camarero Specifications



## Camarero DS100T3U-26R4

### Key features

- Intel® Xeon® processor 5600/5500 series, with QPI up to 6.4 GT/s
- 288GB\*\* DDR3 1333/ 1066/ 800MHz ECC Registered DIMM / 48GB Unbuffered DIMM
- Left: (Full-height / Full-length) 1 (x8) PCI-E 2.0, 2 (x4) PCI-E 2.0 and UIO slot , Right: 2 (x4) PCI-E 2.0 slots
- 2x Intel® 82576 Dual-port Gigabit Ethernet Controllers (4 ports)
- 8 x 3.5" Hot-swap Drives Trays
- 920W High-efficiency Platinum Level Redundant Power Supply
- Integrated IPMI 2.0 with Dedicated LAN



Processor/Cache	
Processor	Intel® Xeon® processor 5600/5500 Series
Intel® 5520 (Tylersburg) chipset	
Memory Capacity	18x 240-pin DIMM slots. Supports up to 288GB 1333 / 1066 / 800MHz DDR3 ECC Registered memory
PCI-Express	Left:1 x PCI-Express x16 Full-Height 2 x PCI-Express x8 Full-Height 1 x UIO, Right:3 x PCI-Express Low-Profile
SATA	Intel ICH10R SATA 3.0Gbps Controller. RAID 0, 1, 5, 10 support
RAID Card	Optional
Optical Drive	Optional

Front Panel :	
LED Indicators	Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Power fail LED.
Switches	Power On/Off Button, System Reset Button
Drive bays	
HDD bays	8 x 3.5" Hot-swap Drives Trays
Peripheral Drives	Slim 8x DVD, 24x CD, DVD-ROM Drive
Cooling System	
4x 80mm 6300 RPM fans, 1x Air Shroud	
Power Supply	
720W, 1+1 redundant, 80PLUS Gold	
Form Factor	
2U Rackmount Width- 17.2" (437mm), Height- 3.5" (89mm) , Depth – 27.75" (705mm)	
<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	