

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

Camarero DS20036R-48

## Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Expansion slots: 3 (x16) PCI-E 3.0, 2 (x8) PCI-E 3.0 & 1 (x4) PCI-E 3.0
- Intel® i350 Dual port Gigabit Ethernet
- 8x SAS2 ports via LSA 2308
- 8x Hot-swap 3.5" SATA HDD Bays
- 1200W High Efficiency Power Supply 80 PLUS, Platinum Level (94%)
- Tower or Rackmount



## Processor/Cache

Processor Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

## Chipset

Intel® C606 Chipset

## System Memory

Memory Capacity 16x 240-pin DDR3 DIMM sockets  
Up to 1TB DDR3 ECC LRDIMM  
Up to 512GB DDR3 ECC Registered memory (RDIMM)

## Expansion Slots

PCI-Express 3 (x16) PCI-E 3.0 slots  
2 (x8) PCI-E 3.0 slots  
1 (x4) PCI-E 3.0 slot

## Integrated On-Board

SAS SAS2 via LSI 2308 RAID 0, 1, 10 support  
SATA SATA 2.0 3Gbps with RAID 0, 1, 5, 10  
SATA 3.0 6Gbps with RAID 0, 1  
LAN 2x RJ45 Gigabit Ethernet LAN ports

## Add-on Options

Optical Drive Optional

## Front Panel :

LED Indicators Power LED Hard drive activity LED 2x  
Network activity LEDs System Overheat /  
Fan Fail LED  
Switches Power On/Off button System Reset button

## Drive bays

HDD bays 8x Hot-swap 3.5" SATA Drive Trays  
Peripheral Bays 2x 5.25" Peripheral Drive Bay 1x 5.25"  
Bay for Floppy Drive

## Power Supply

1200W High Efficiency Power Supply 80 PLUS, Platinum  
Level (94%)

## Cooling System

2x 80mm PWM Super Quiet Fans  
1x 92mm PWM Super Quiet Rear Fan

## Form Factor

4U Rackmountable / Tower  
Height 17.8" (452mm)  
Width 7.0" (178mm)  
Depth 25.5" (648mm)

**E : [info@tyronesystems.com](mailto:info@tyronesystems.com)**

**For more/current product information, visit  
[www.tyronesystems.com](http://www.tyronesystems.com)**