## **Tyrone Camarero Specifications**

# Tyrone

### Camerero DS2003TG-210R

#### **Key features**

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family†
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 6x PCI-E 3.0 x16 slots (support GPU/Xeon Phi cards, opt.), 1x PCI-E 3.0 x8 (in x16) low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 10x Hot-swap 2.5" SATA Drive Bays
- 1800W Redundant Power Supplies Platinum Level (94%+)
- 5x heavy duty cooling fans
- Smart server management tools





#### Processor/Cache

Processor Dual socket R (LGA 2011) supports

Intel®Xeon® processor E5-2600 and

E5-2600 v2 family†

#### Chipset

Intel® C602 Chipset

#### System Memory

8x 240-pin DDR3 DIMM sockets **Memory Capacity** 

Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered

memory (RDIMM)

#### **Expansion Slots**

**PCI-Express** 6x PCI-E 3.0 x16 slots (support

GPU/Xeon Phi cards, option)

1x PCI-E 3.0 x8 (in x16) low-profile slot

#### Integrated On-Board

Intel ICH10R SATA 3.0Gbps Controller **SATA** 

RAID 0, 1, 5, 10 support

LAN 2 RJ45 Gigabit Ethernet LAN ports

1 RJ45 Dedicated IPMI LAN port

#### **Add-on Options**

RAID Card Optional **Optical Drive** 

None

#### Front Panel:

**LED Indicators** 2x Network activity LEDs System

Overheat LED / Fan fail LED / UID LED

**Switches** Power On/Off Button

#### Drive bays

HDD bays 10x 2.5" Hot-swap drive bays

#### **Power Supply**

1800W Redundant Power Supplies Platinum Level (94%+)

#### Cooling System

5x 8cm heavy duty fans with optimal fan speed control

#### Form Factor

2U Rackmount

Width- 17.2" (437mm), Height- 3.5" (89mm), Depth - 31" (787mm)

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com