

Tyrone Camarero Specifications

Tyrone

Camarero DS2007T1-224R

Key Features:

Four hot-pluggable systems (nodes) in a 2U form factor.

Each node supports the following:

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 (x16) low-profile slot
- Intel® i350 Dual port Gigabit Ethernet
- 6x Hot-swap 2.5" SATA3/SAS2 HDD Bays
- 1620W Redundant Power Supplies 80 PLUS, Platinum Level (94%)



<h3>Processor/Cache</h3>	<h3>Front Panel :</h3>										
<table border="0"> <tr> <td>Processor</td> <td>Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family</td> </tr> </table>	Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	<table border="0"> <tr> <td>LED Indicators</td> <td>Power LED/Hard drive activity LED / 2x Network activity LEDs /System Overheat LED</td> </tr> <tr> <td>Buttons</td> <td>Power On/Off button System Reset button UID button</td> </tr> </table>	LED Indicators	Power LED/Hard drive activity LED / 2x Network activity LEDs /System Overheat LED	Buttons	Power On/Off button System Reset button UID button				
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family										
LED Indicators	Power LED/Hard drive activity LED / 2x Network activity LEDs /System Overheat LED										
Buttons	Power On/Off button System Reset button UID button										
<h3>Chipset</h3>	<h3>Drive bays</h3>										
<table border="0"> <tr> <td>Intel® C602 Chipset</td> <td></td> </tr> </table>	Intel® C602 Chipset		<table border="0"> <tr> <td>HDD bays</td> <td>6x Hot-swap 2.5" SATA3/SAS2 HDD trays</td> </tr> </table>	HDD bays	6x Hot-swap 2.5" SATA3/SAS2 HDD trays						
Intel® C602 Chipset											
HDD bays	6x Hot-swap 2.5" SATA3/SAS2 HDD trays										
<h3>System Memory</h3>	<h3>Power Supply</h3>										
<table border="0"> <tr> <td>Memory Capacity</td> <td>8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)</td> </tr> </table>	Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)	<table border="0"> <tr> <td></td> <td>1620W Redundant Power Supplies 80 PLUS, Platinum Level (94%+)</td> </tr> </table>		1620W Redundant Power Supplies 80 PLUS, Platinum Level (94%+)						
Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)										
	1620W Redundant Power Supplies 80 PLUS, Platinum Level (94%+)										
<h3>Expansion Slots</h3>	<h3>Cooling System</h3>										
<table border="0"> <tr> <td>PCI-Express</td> <td>1x PCI-E 3.0 (x16) Low-profile slot</td> </tr> </table>	PCI-Express	1x PCI-E 3.0 (x16) Low-profile slot	<table border="0"> <tr> <td></td> <td>4x 8cm heavy duty PWM fans with optimal fan speed control</td> </tr> </table>		4x 8cm heavy duty PWM fans with optimal fan speed control						
PCI-Express	1x PCI-E 3.0 (x16) Low-profile slot										
	4x 8cm heavy duty PWM fans with optimal fan speed control										
<h3>Integrated On-Board</h3>	<h3>Form Factor</h3>										
<table border="0"> <tr> <td>SATA</td> <td>SATA 2.0 & 3.0 with RAID 0, 1, 5, 10</td> </tr> <tr> <td>SAS</td> <td>LSI 2108 SAS (6Gbps) w/ Hardware RAID support</td> </tr> <tr> <td>LAN</td> <td>RAID 0, 1, 5, 6, 10, 50, 60 support 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45</td> </tr> <tr> <td></td> <td>Dedicated IPMI LAN port</td> </tr> </table>	SATA	SATA 2.0 & 3.0 with RAID 0, 1, 5, 10	SAS	LSI 2108 SAS (6Gbps) w/ Hardware RAID support	LAN	RAID 0, 1, 5, 6, 10, 50, 60 support 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45		Dedicated IPMI LAN port	<table border="0"> <tr> <td></td> <td>2U Rackmount, Width – 17.25" (438mm), Height - 3.47" (88mm), Depth - 26.75" (679mm)</td> </tr> </table>		2U Rackmount, Width – 17.25" (438mm), Height - 3.47" (88mm), Depth - 26.75" (679mm)
SATA	SATA 2.0 & 3.0 with RAID 0, 1, 5, 10										
SAS	LSI 2108 SAS (6Gbps) w/ Hardware RAID support										
LAN	RAID 0, 1, 5, 6, 10, 50, 60 support 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45										
	Dedicated IPMI LAN port										
	2U Rackmount, Width – 17.25" (438mm), Height - 3.47" (88mm), Depth - 26.75" (679mm)										
<h3>Add-on Options</h3>	<p style="text-align: center;">Email : info@tyronesystems.com</p>										
<table border="0"> <tr> <td>Optical Drive</td> <td>None</td> </tr> <tr> <td>Raid</td> <td>Optional</td> </tr> </table>	Optical Drive	None	Raid	Optional	<p style="text-align: center;">For more/current product information, visit www.tyronesystems.com</p>						
Optical Drive	None										
Raid	Optional										