

Tyrone Camarero Specifications



Camarero DS200T3G-14-2075

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 4x M2075 GPU cards pre-installed
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 4x Hot-swap 2.5" SATA Drive Bays
- 1800W Power Supply w/ PMBusV 80Plus Platinum Level (94%+)
- 12x Cooling Fans Total
- Smart server management tools



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM
Expansion Slots	
PCI-Express	4x M2075 GPU cards pre-installed
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	Power LED,Hard drive activity LED,2x Network activity LEDs,System Overheat LED / Fan fail LED /UID LED
Switches	Power On/Off button,System Reset button
Drive bays	
HDD bays	4x 2.5" Hot-swap drive bays
Power Supply	
	1800W Power Supply w/ PMBus Platinum Level (94%+)
Cooling System	
	12x Counter-rotating Fans with optimal fan speed control
Form Factor	
	1U Rackmount
Height	1.7" (43mm),
Width	17.2" (437mm),
Depth	31" (787mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners