

# Tyrone Camarero Specifications

# Tyrone

Camarero DS200T3G-14

## Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 4 (x16) PCI-E 3.0 slots (GPU card opt.) 1 (x8) PCI-E 3.0 (in x16) low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 4x Hot-swap 2.5" SATA Drive Bays
- 1800W Power Supply w/ PMBus Platinum Level (94%+) power supply
- 12x Cooling Fans Total
- Smart server management tools



<b>Processor/Cache</b>		<b>Front Panel :</b>	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
Switches		Switches	Power On/Off Button, System Reset Button
<b>Chipset</b>		<b>Drive bays</b>	
Intel® C602 Chipset		HDD bays	4x 2.5" Hot-swap drive bays
<b>System Memory</b>		<b>Power Supply</b>	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)	1800W Power Supply w/ PMBus Platinum Level (94%+) power supply	
<b>Expansion Slots</b>		<b>Cooling System</b>	
PCI-Express	4 (x16) PCI-E 3.0 slots 1 (x8) PCI-E 3.0 (in x16) low-profile slot Supports 4 GPU cards (one via riser card RSC-R1UG-E16BR-X9-O-P)	12x Counter-rotating Fans with optimal fan speed control cooling systems	
<b>Integrated On-Board</b>		<b>Form Factor</b>	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1	1U Rackmount Height 1.7" (43mm), Width 17.2" (437mm), Depth 31" (787mm)	
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port		
<b>Add-on Options</b>		<b>E : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b> <b>For more/current product information, visit</b> <b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b>	
RAID Card	Optional		
Optical Drive	None		