

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS200T3G-14RT

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 3 (x16) PCI-E 3.0 slots (GPU card opt.) 1 (x8) PCI-E 3.0 (in x16) low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® X540 10GBase-T Controller
- 4x Hot-swap 2.5" SATA3 Drive Bays
- 1800W Redundant Power Supplies 80Plus Platinum Level (94%+)
- 10x Counter rotating fans w/ optimal fan speed control
- Smart server management tools
- Intel® Xeon Phi™ Support



Processor/Cache	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
Chipset	
	Intel® C602 Chipset
System Memory	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)
Expansion Slots	
PCI-Express	3 (x16) PCI-E 3.0 slots (GPU card option) 1 (x8) PCI-E 3.0 (in x16) low-profile slot
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1
LAN	2x RJ45 10GBase-T port * 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Raid	Optional
Optical Drive	None

Front Panel	
LED	Power LED, Hard drive activity LED, 2x Network activity LEDs # System Overheat LED / Fan fail LED / UID LED
Switches	Power On/Off Button
Drive Bays	
HDD Bays	4x 2.5" Hot-swap drive bays
Peripheral Bays	None
Power Supply	
	1800W Redundant Power Supplies 80Plus Platinum Level (94%+)
Cooling System	
	10x counter-rotating fans with optimal fan speed control
Form Factor	
	1U Rackmount, Height * 1.7" (43mm), Width * 17.2" (437mm), Depth * 28.2" (716mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	