

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS200T3G-14T

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 4 (x16) PCI-E 3.0 slots (GPU card opt.) 1 (x8) PCI-E 3.0 (in x16) low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® X540 10GBase-T Controller
- 4x Hot-swap 2.5" SATA3 Drive Bays
- 1800W Power Supply w/ PMBus 80Plus Platinum Level (94%+)
- 12x Cooling Fans Total
- Smart server management tools



Processor/Cache		Front Panel	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	Power status LED Hard drive activity LED 2x Network activity LEDs System Overheat & Power Fail LED
		Buttons	Power On/Off Button, System Reset Button
Chipset		Drive Bays	
Chipset	Intel® C602 Chipset	HDD bays	4x 2.5" Hot-swap drive bays
System Memory		Power Supply	
Memory Capacity	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)		1800W Power Supply w/ PMBus 80Plus Platinum Level (94%+)
Expansion Slots		Cooling System	
PCI-Express	4 (x16) PCI-E 3.0 slots 1 (x8) PCI-E 3.0 (in x16) low-profile slot Supports 4 GPU cards (one via riser card RSC-R1UG-E16BR-X9-O-P)		12x Counter-rotating Fans with optimal fan speed control
Integrated On-Board		Form Factor	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1	Form Factor	1U Rackmountable
LAN	2x RJ45 10GBase-T ports 1 RJ45 Dedicated IPMI LAN port	Height	: 1.7" (43mm),
		Width	: 17.2" (437mm),
		Depth	: 31" (787mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	None		