Tyrone Camarero Specifications

Tyrone®

Camerero DS200T3G-48R


Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- 4 PCI-E 3.0 x16 (4x double-width GPU cards opt.), 2 PCI-E 3.0 x8 (1 in x16), 1 PCI-E 2.0 x4 (in x8)
- I/O ports: 1 VGA, 2 COM, 2 GbE, 10 USB 2.0, & 1 IPMI Dedicated LAN
- 8x Hot-swap 3.5", 3x Fixed 5.25" and 1x Fixed 3.5" Drive Bays
- (For Passive Configuration) 4x Heavy Duty Fans, 4x Exhaust Fans,
- and 2x Active Heatsink with Optimal Fan Speed Control
 (For Active Configuration) 4x 92x38mm 4-pin PWM Middle Cooling Fans, 2x 80x38mm 4-pin PWM Rear Exhaust Fans
- 1620W Redundant Power Supplies 80 PLUS, Platinum Level (94%)
- Tower or Rackmount



Xeon

Xeon Phi



0 Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries

O Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners