

Tyrone Camarero Specifications

Tyrone

Camarero DS200T3R-28R



Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 1x PCI-E 3.0 x16 slot and 4x PCI-E 3.0 x8 slots
- Intel® i350 Dual port Gigabit
- 8x Hot-swap 3.5" SATA HDD Bays
- 740W Redundant Power Supplies 80 Plus, Platinum Level
- Power Saving Optimized & Improved Cooling, PUE-Optimized: 0°C ~ 47°C



Processor/Cache

Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

Chipset

Intel® C602 Chipset

System Memory:

8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)

Expansion Slots:

2x PCI-E 3.0 x16 Full-height, Half-length slots

Integrated On-Board

SATA 2.0 (3Gbps) & 3.0 (6Gbps) with RAID 0, 1, 5, 10 (Optional)

LAN: 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID card optional

Optical Drive : Optional

Front Panel :

LED Indicators: Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED Power fail LED

Switches: Power On/Off Button, System Reset Button

Drive bays

HDD bays 8x Hot-swap 3.5" SATA HDD Bays

Peripheral Bays: Slim DVD-ROM drive (optional)

Power Supply

740W Redundant Power Supplies 80 Plus, Platinum Level

Cooling System

3x 8cm 7k RPM middle fans

Form Factor

2U Rack mount

Width 17.2" (437mm) , Height 3.5" (89mm) , Depth 25.5" (648mm)

Email : info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com