Tyrone Camarero Specifications

Tyrone

Camerero DS200T3T-212R

Two hot-pluggable systems (nodes) in a 2U form factor. Each node supports the following

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 3x PCI-E 3.0 (x8) slots via riser card (1x Low-profile and 2x Full-height Full-length
- Intel® i350 Dual port Gigabit
- 6x 3.5" Hot-swap SATA3/SATA2 HDD Bays
- 1280W Redundant Power Supplies 80 PLUS, Platinum Level
- Support 1 Full-height Full-length PCI-E x16 GPU card per node w/ GPU Kit





•						•	_		
Jr	\sim	\boldsymbol{c}	$^{\circ}$	C	\sim	r/I	Ca	n	

Processor Dual socket R (LGA 2011) supports

Intel® Xeon® processor E5-2600 and

E5-2600 v2 family

Chipset

Chipset Intel® C602 ChipsetIntel® C602 chipset

System Memory

Memory Capacity 8x 240-pin DDR3 DIMM sockets

Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered

memory (RDIMM)

Expansion Slots

PCI-Express 3x PCI-E 3.0 (x8) slots via riser card

(1x Low-profile and 2x Full-height

Full-length)

Integrated On-Board

SATA SATA 2.0 & 3.0 with RAID 0, 1, 5, 10

LAN 2x RJ45 Gigabit Ethernet LAN ports

1x RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Optional

Optical Drive None

Front Panel

LED Indicators Power LED, Hard drive activity LED,

2x Network activity LEDs Universal

Information (UID) LED

Switches Power On/Off Button,

System Reset Button

Drive Bays

HDD bays 6x 3.5" Hot-swap SATA3/SATA2 HDD Bays

Peripheral Bays None

Power Supply

Power Supply 1280W Redundant Power Supplies

80 PLUS, Platinum Level

Cooling System

Cooling System 4x 8cm heavy duty PWM fans with

optimal fan speed control

Form Factor

2U Rack mount

Width: 17.25" (438mm), Height: 3.47" (88mm), Depth: 28.5" (724mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com