

Tyrone Camarero Specifications

Tyrone

Camarero DS200T3T-212RI

Key Features:

Two hot-pluggable systems (nodes) in a 2U form factor.

Each node supports the following:

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3. up to 1866MHz: 8x DIMM sockets
- 3x PCI-E 3.0 (x8) slots (1x low-profile and 2x full-height full-length)
- Intel® i350 Dual port Gigabit
- HDD Bays- 6 x hotswap 3.5" SATA3/SAS HDD Trays
- 1280W Redundant Power Supplies 80 PLUS, Platinum Level
- Support 1 Full-height Full-length PCI-E x16 GPU card per node w/ GPU Kit



Processor/Cache

Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

Chipset

Intel® C602 Chipset

System Memory:

8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM Up to 256GB DDR3 ECC Registered memory (RDIMM)

Expansion Slots:

3x PCI-E 3.0 (x8) slots (1x low-profile and 2x full-height full-length)

Integrated On-Board

SATA:SATA 2.0 & 3.0 with RAID 0, 1, 5, 10
LAN:2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID card optional
Optical Drive :None

Front Panel :

LED Indicators: Power LED,Hard drive activity LED, 2x Network activity LEDs,Universal Information (UID) LED
Switches:Power On/Off Button,System Reset Button, UID Button

Drive bays

HDD bays : HDD Bays- 6 x hotswap 3.5" SATA3/SAS HDD Trays
Peripheral Bays:None

Power Supply

1280W Redundant Power Supplies 80 PLUS, Platinum Level

Cooling System

4x 8cm heavy duty PWM fans with optimal fan speed control

Form Factor

2U Rackmount
Width 17.25" (438mm),
Height 3.47" (88mm),
Depth 28.5" (724mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com