

# Tyrone Camarero Specifications

# Tyrone

## Camarero DS200T6G-14R-2090



### Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- 3x M2090 GPU cards pre-installed, 1 (x8) PCI-E 3.0 (in x16) low-profile slot
- Integrated IPMI 2.0 with KVM and Dedicated LAN
- Intel® i350 Dual-Port GbE Controller
- 4x Hot-swap 2.5" SATA Drive Bays
- 1800W Redundant Power Supplies 80Plus Platinum Level
- 10x Counter rotating fans w/ optimal fan speed control
- Smart server management tools



### Processor/Cache

Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

### Chipset

Intel ® C602 Chipset

### System Memory

8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM  
Up to 256GB DDR3 ECC Registered memory (RDIMM)

### Expansion Slots:

3 (x16) PCI-E 3.0 slots (3x NVIDIA Tesla M2090 Fermi GPU cards integrated) 1 (x8) PCI-E 3.0 (in x16) low-profile slot

### Integrated On-Board

SATA:SATA 2.0 3Gbps with RAID 0, 1, 5, 10  
SATA 3.0 6Gbps with RAID 0, 1

LAN:2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated

IPMI LAN port

### Add-on Options

RAID card optional

Optical Drive :None

### Front Panel :

LED Indicators: Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Universal Information (UID) LED  
Switches: Power On/Off Button, System Reset Button

### Drive bays

HDD bays 4 x 2.5" Hot-swap drive bays

Peripheral Bays :None

### Power Supply

1800W Redundant Power Supplies 80Plus Platinum Level

### Cooling System

10x counter-rotating fans with optimal fan speed control

### Form Factor

1U Rackmount

Height 1.7" (43mm)

Width 17.2" (437mm)

Depth 31" (787mm)

Email : [info@tyronesystems.com](mailto:info@tyronesystems.com)

For more/current product information, visit

[www.tyronesystems.com](http://www.tyronesystems.com)