

# Tyrone Camarero Specifications



## Camarero DS200T6R-45RX

### Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Expansion slots: 10x PCI-E 3.0 x8, 1x PCI-E 2.0 x4 (in x8)
- Intel® i350 Dual port Gigabit Ethernet
- 5x 3.5" Hot-swap HDD Bays
- 3x 5.25" Peripheral Drive Bays
- 600W Redundant Power Supplies 80 PLUS, Platinum Level (94%)



| Processor/Cache     |  |
|---------------------|--|
| Processor           | Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family                       |
| Chipset             |  |
| Intel® C602 Chipset |  |
| System Memory       |  |
| Memory Capacity     | 16x 240-pin DDR3 DIMM sockets<br>Up to 1TB DDR3 ECC LRDIMM<br>Up to 512GB DDR3 ECC Registered memory (RDIMM) |
| Expansion Slots     |  |
| PCI-Express         | 10x PCI-E 3.0 x8<br>1x PCI-E 2.0 x4 (in x8)  |
| Integrated On-Board |  |
| SATA                | SATA 2.0 3Gbps with RAID 0, 1, 5, 10<br>SATA 3.0 6Gbps with RAID 0, 1, 5, 10                                 |
| LAN                 | 2x RJ45 Gigabit Ethernet LAN ports<br>1x RJ45 Dedicated IPMI LAN port  |
| Add-on Options      |  |
| RAID Card           | Optional   |
| Optical Drive       | Optional   |

| Front Panel :   |   |
|---|---|
| LED Indicators  | Power LED Hard drive activity LED 2x Network activity |
| Switches  | Power On/Off button System Reset button               |
| Drive bays  |   |
| HDD bays  | 5x 3.5" Hot-swap Drive Trays                          |
| Peripheral Bays   | 3x 5.25" Peripheral Drive Trays                       |
| Power Supply  |   |
| 600W Redundant Power Supplies   | 80 PLUS, Platinum Level (94%)                         |
| Cooling System  |   |
| 1x 92x38mm 4-pin PWM front intake fan   |   |
| 2x 80x38mm 4-pin PWM rear exhaust fans  |   |
| Form Factor   |   |
| 4U Rack mountable / Tower   |   |
| Height  | :17.2" (437mm),                                       |
| Width   | :7.0" (178mm),  |
| Depth   | :20.5" (521mm)  |
| <p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit <a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p> |   |