

Tyrone Camarero Specifications



Camarero DS200T6W-14

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Add on card support: 2x PCI-E 3.0 x16 Full-height, Half-length slots
- Intel® i350 Dual port Gigabit Ethernet Controller; 2x LAN ports
- 4x Hot-swap 3.5" SAS/SATA2 HDD Bays Connected to on board storage controller
- 600W High-efficiency Power Supply Platinum Level (94%)



Processor/Cache

Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family

Chipset

Intel® C602 Chipset

System Memory:

16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)

Expansion Slots:

2x PCI-E 3.0 x16 Full-height, Half-length slots

Integrated On-Board

SATA Via Cable for SATA controller SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1
LAN 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port

Add-on Options

RAID Optional

Optical Drive : Optional

Front Panel :

LED Indicators: Power LED, Hard drive activity LED, 2x Network activity LEDs, System Overheat LED, Universal Information (UID) LED
Switches: Power On/Off Button, System Reset Button, UID Button

Drive bays

HDD bays 4x Hot-swap 3.5" SAS / SATA2 HDD trays
Peripheral Bays : Slim DVD-ROM drive (optional)

Power Supply

600W High-efficiency Power Supply Platinum Level (94%)

Cooling System

5x 4cm Counter-rotating PWM fans

Form Factor

1U Rackmount

Width 17.2" (437mm)
Height 1.7" (43mm)
Depth 25.6" (650mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com