

Tyrone Camarero Specifications



Camarero DS200T6W-14R

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 1TB ECC DDR3, up to 1866MHz; 16x DIMM sockets
- Add on card support: 2x PCI-E 3.0 x16 Full-height, Half-length slots
- Intel® i350 Dual port Gigabit Ethernet Controller; 2x LAN ports
- 4x Hot-swap 3.5" SAS/SATA2 HDD Bays Connected to on board storage controller
- 700W Redundant Power Supplies 80 PLUS



Processor/Cache		Front Panel	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LED Indicators	Power LED Hard drive HDD activity 2x Network activity LEDs Universal Information (UID) LED
Switches		Switches	Power On/Off button System Reset button UID button
Chipset		Drive Bays	
	Intel® C602 Chipset	HDD bays	4x Hot-swap 3.5" SAS / SATA HDD trays
		Peripheral Bays	Slim DVD-ROM drive (Optional)
System Memory		Power Supply	
Memory Capacity	16x 240-pin DDR3 DIMM sockets Up to 1TB DDR3 ECC LRDIMM Up to 512GB DDR3 ECC Registered memory (RDIMM)		700W Redundant Power Supplies,80 PLUS, Gold Level Certified
Expansion Slots		Cooling System	
PCI-Express	2x PCI-E 3.0 x16 Full-height, Half-length		5x 4cm Counter-rotating PWM fans
Integrated On-Board		Form Factor	
SATA	Via SATA directly SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1		1U Rackmount
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		Width 17.2" (437mm), Height 1.7" (43mm), Depth 25.6" (650mm),
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid Card	Optional		
Optical Drive	Optional		