

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS200TR-34

Key features

- Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family
- Up to 512GB ECC DDR3, up to 1866MHz; 8x DIMM sockets
- Intel® C602 chipset
- 3 PCI-E 3.0 x8, 1 PCI-E 2.0 x4 (in x8), 1 PCI-E 2.0 x1, 1 PCI
- Intel® 82574L GbE LAN, 2 ports
- 8x SATA2 and 2x SATA3 ports
- 4x 3.5" internal SAS/SATA HDD Bays, 4x 2.5" internal SAS/SATA HDD (opt.)
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 500W High Efficiency Power Supply
- Cost Effective Desktop, Embedded, Workstation Chassis



Processor/Cache		Front Panel	
Processor	Dual socket R (LGA 2011) supports Intel® Xeon® processor E5-2600 and E5-2600 v2 family	LEDs	Power LED, Hard drive activity LED, Network activity LED, System Overheat LED
Chipset	Intel® C602 chipset	Buttons	Power On/Off button
System Memory	8x 240-pin DDR3 DIMM sockets Up to 512GB DDR3 ECC LRDIMM	Drive Bays	HDD Bays (Internal) 4x 3.5" internal SAS/SATA HDD Bays. 4x 2.5" internal SAS/SATA HDD (opt.) Peripheral Bay 2x 5.25" peripheral drive bays 1x 3.5"
Expansion Slots	3 PCI-E 3.0 x8, 1 PCI-E 2.0 x4 (in x8), 1 PCI-E 2.0 x1, 1 PCI	Power Supply	500W High Efficiency Power Supply
Integrated On-Board	SATA SATA 2.0 3Gbps with RAID 0, 1, 5, 10. SATA 3.0 6Gbps with RAID 0, 1, 5, 10 LAN 2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port	Cooling System	1x 12cm (1850rpm) rear exhaust fan, 1x 12cm (1850rpm) front cooling fan. Optimized Cooling Technology at 21dB Whisper-Quiet Operation
Add-on Options	RAID Card Optional Optical Drive Optional	Form Factor	Mid Tower Dimensions Width (7.6" (193 mm), Height (16.7" (424 mm), Depth (20.68" (525.3 mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	