

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS2BOT3R-18

Key features

- Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2
- Up to 192GB DDR3 1600MHz ECC R/LRDIMM; 6x DIMM sockets
- 1 PCI-E 3.0 x16 Expansion slot (FHFL)
- Intel® 82574L GbE LAN, 2 ports
- 8x Hot-swap 2.5" SATA HDD Bays
- 600W High-efficiency Power Supply with Digital Switching Control
- 1U Short Depth - 19.98" (508mm)



Processor/Cache	
Processor family	Intel® Xeon® processors E5-2400 v2
Chipset	
	Intel® C602 Chipset
System Memory	
Memory Capacity	6x 240-pin DDR3 DIMM sockets Supports up to 192 GB DDR3 ECC
Expansion Slots	
PCI-Express	1x PCI-E 3.0 x16 Full-height Half-length
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1, 5, 10
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional
Optical Drive	None

Front Panel :	
LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
Switches	Power On/Off Button, System Reset Button
Drive bays	
HDD bays	8x Hot-swap 2.5" SATA HDD trays
Power Supply	
	600W High-efficiency Power Supply with Digital Switching Control
Cooling System	
	4x 40x28mm high-efficiency PWM fans (Optional 2x fans for AOC cooling)
Form Factor	
	1U Rackmount
Width	17.2" (437mm),
Height	1.7" (43mm),
Depth	19.98" (507.5mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	

Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries

Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners