

Tyrone Camarero Specifications

Tyrone

Camarero DS2B0T3R-34

Key features

- Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2
- Intel® C602 chipset; QPI up to 8 GT/s
- Up to 192GB DDR3 1600MHz ECC Registered DIMM; 6x DIMM sockets
- Expansion slots: 1 PCI 32, 1 PCI-E 3.0 x16, 1 PCI-E 3.0 x4 (in x8), 3 PCI-E 3.0 x8 (1 allows a x16 card)
- I/O Ports: 1 COM, 2 GbE LAN, 4 USB 3.0 (2 Rear, 2 Front), 6 USB 2.0 (4 Rear, 2 Front), 1 Audio 7.1 HD
- 4x Fixed 3.5" Drive Bays + Optional 4x Fixed 2.5" SATA2/3 HDD Bays
- 500W High Efficiency Power Supply



Processor/Cache

Processor Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2

Chipset

Intel® C602 Chipset

System Memory

Memory Capacity 6x 240-pin DDR3 DIMM sockets Supports up to 192 GB DDR3 ECC Registered memory (RDIMM)

Expansion Slots

PCI-Express 1x PCI-E 3.0 x16
3x PCI-E 3.0 x8 (1 allows a x16 card)
1x PCI-32

Integrated On-Board

SATA SATA 2.0 3Gbps with RAID 0, 1, 5, 10
SATA 3.0 6Gbps with RAID 0, 1, 5, 10

LAN 2x RJ45 Gigabit Ethernet LAN ports

Add-on Options

RAID Card Optional

Front Panel :

LED Indicators Power LED Hard drive activity LED 2x Network activity LEDs System Overheat LED / Fan fail LED / UID LED

Switches Power On/Off button

Drive bays

HDD bays 4x Fixed 3.5" Drive Bays 4x Fixed 2.5" Drive Bays (optional) Enterprise SATA| HDD only recommended

Power Supply

500W High Efficiency Power Supply

Cooling System

1x12cm rear exhaust fan with Optimal Fan Speed Control
Optimized cooling technology for Whisper-Quiet Operation

Form Factor

Mid-Tower
Height : 16.7" (424mm),
Width : 7.6" (193mm),
Depth : 20.68" (525.3mm)

E : info@tyronesystems.com

**For more/current product information, visit
www.tyronesystems.com**