

Tyrone Camarero Specifications



Camarero DS2B0T3U-14R

Key features

- Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2
- Up to 384GB DDR3 1600MHz ECC R/LRDIMM; 12x DIMM sockets
- 1x UIO, 1x PCI-E 3.0 x8 Full-height Full-length Expansion Slot
- Intel® i350 Dual port Gigabyte Ethernet Controller; 2x LAN ports
- 4x Hot-swap 3.5" SAS/SATA HDD Bays for Customizable Storage
- 500W Redundant Power Supplies Platinum Level (94%+)



Processor/Cache		Front Panel :	
Processor	Intel® Xeon® processor E5-2400 v2	LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
		Switches	Power On/Off button, System Reset button, UID button
Chipset		Drive bays	
	Intel® C602 Chipset	HDD bays	4x Hot-swap 3.5" SAS / SATA HDD trays
		Peripheral Bays	Slim DVD-ROM drive (optional)
System Memory		Power Supply	
Memory Capacity	12x 240-pin DDR3 DIMM sockets Supports up to 384 GB DDR3 ECC		500W Redundant Power Supplies Platinum Level (94%+)
Expansion Slots		Cooling System	
PCI-Express	1x UIO 1x PCI-E 3.0 x8 Full-height Full-length		4x 4cm Counter-rotating PWM fans
Integrated On-Board		Form Factor	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1		1U Rackmount
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port	Width	17.2" (437mm),
		Height	1.7" (43mm),
		Depth	25.6" (650mm)
Add-on Options		<p>Email: info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
RAID Card	Optional		
Optical Drive	Optional		