

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS2BOT6R-14R

Key features

- Dual socket B2 (LGA 1356) supports Intel® Xeon® processor E5-2400 v2
- Up to 192GB DDR3 1600MHz ECC R/LRDIMM; 6x DIMM sockets
- 1 PCI-E 3.0 x16 Expansion slot (FHFL)
- Intel® 82574L GbE LAN, 2 ports
- 4x Hot-swap 3.5" SATA HDD Bays
- 400W Redundant Power Supplies Optional Battery Backup Power
- 1U Short Depth - 19.8" (503mm)



Processor/Cache	
Processor	Intel® Xeon® processor E5-2400 v2
Chipset	
Intel® C602 Chipset	
System Memory	
Memory Capacity	6x 240-pin DDR3 DIMM sockets Supports up to 192 GB DDR3 ECC
Expansion Slots	
PCI-Express	1x PCI-E 3.0 x16 Full-height Half-length
Integrated On-Board	
SATA	SATA 2.0 3Gbps with RAID 0, 1, 5, 10 SATA 3.0 6Gbps with RAID 0, 1, 5, 10
LAN	2 RJ45 Gigabit Ethernet LAN ports 1 RJ45 Dedicated IPMI LAN port
Add-on Options	
RAID Card	Optional

Front Panel :	
LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
Switches	Power On/Off Button, System Reset Button
Drive bays	
HDD bays	4x Hot-swap 3.5" SATA HDD trays
Power Supply	
400W Redundant Power Supplies Optional Battery Backup Power	
Cooling System	
4x 4cm 12,500 RPM PWM fans	
Form Factor	
1U Rackmount	
Width	17.2" (437mm),
Height	1.7" (43mm),
Depth	19.8" (503mm)

Email: info@tyronesystems.com
For more/current product information, visit
www.tyronesystems.com