

# Tyrone Camarero Specifications

**Tyrone**<sup>®</sup>

Camarero DS3007E1-216RT

## Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 16x DIMM slots
- 1x PCI-E 3.0 x16, 6x PCI-E 3.0 x8
- Dual 10GBase-T LAN w/ Intel® X540
- 16x 3.5" Hot-swap SAS3 drive bays; 2x 2.5" optional Hot-swap drive bays (rear)
- SAS3 via LSI 3108 controller, HW RAID
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 4x 8cm hot-swap redundant PWM cooling fans
- 1000W Redundant Power Supplies Titanium Level



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LED Indicators	Power status LED Hard drive activity LED 2x Network activity LEDs System Overheat & Power Fail LED
		Buttons	Power On/Off Button, System Reset Button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD bays	16x 3.5" Hot-swap SAS3 drive bays
		Optional	2x 2.5" Hot-swap drive bays (rear)
System Memory		Power Supply	
Memory Capacity	16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 512 ECC RDIMM		1000W Redundant Power Supplies Titanium Level
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16 slot 6x PCI-E 3.0 x8 slots		4x 8cm hot-swap redundant PWM cooling fans
Integrated On-Board		Form Factor	
SAS	SAS3 (12Gbps) via LSI 3108 controllers; HW RAID	Form Factor	2U Rackmount
LAN	2x RJ45 10GBase-T LAN ports, 1x RJ45 Dedicated IPMI LAN port	Width:	17.2" (437mm),
		Height:	3.5" (89mm),
		Depth:	25.5" (647mm)
Add-on Options		<p><b>Email : <a href="mailto:info@tyronesystems.com">info@tyronesystems.com</a></b></p> <p><b>For more/current product information, visit</b></p> <p><b><a href="http://www.tyronesystems.com">www.tyronesystems.com</a></b></p>	
Optical Drive	None		