Tyrone Camarero Specifications

Camarero DS3007R-212R

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM, up to DDR4- 2400 MHz; 16x DIMM slots
- 1x PCI-E 3.0 x16, 6x PCI-E 3.0 x8 slots
- Intel® i350 Dual port GbE LAN
- 10x SATA3 (6Gbps) ports w/ Intel C612 controller; RAID 0, 1, 5, 10
- 8x SAS3 (12Gbps) ports w/ LSI 3108 controller (2GB cache); RAID 0, 1, 5, 6, 10, 50, 60
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 5x USB 3.0 and 4x USB 2.0 ports
- 12x 3.5" Hot-swap SAS3/SATA Drive Bays.
- Optional 2x 2.5" Hot-swap SATA3 Drive Bays for OS mirroring
- 3x 80mm 7K RPM Chassis middle fan w/ housing
- 920W Redundant Power Supplies Platinum Level (94%)





Processor/Cache

Dual socket R3 (LGA 2011) supports Processor

Intel® Xeon® processor E5-2600 v4/ v3 family

Chipset

Intel® C612 chipset Chipset

System Memory

Memory Capacity 16x 288-pin DDR4 DIMM slots,

Up to 2TB ECC 3DS LRDIMM,

1TB ECC RDIMM

Expansion Slots

PCI-Express 1x PCI-E 3.0 x16, 6x PCI-E 3.0 x8 slots

Integrated On-Board

LSI 3108 SAS3 (12Gbps) controller; 2GB cache; HW RAID 0, 1, 5, 6, 10, 50, 60. Supports up to 16 devices as default, more HDD devices support is also available as option SAS

SATA SATA3 (6Gbps) with RAID 0, 1, 5, 10 LAN 2x RJ45 Gigabit Ethernet LAN ports,

1x RJ45 Dedicated IPMI LAN port

Add-on Options

Optical Drive None

Front Panel

Buttons Power On/Off button, System Reset button

Drive Bays

HDD bays 12x 3.5" Hot-swap SAS3/SATA3 drive bays.

Optional 2x 2.5" Hot-swap SATA3 Drive Bays for OS

mirroring. SAS or enterprise SATA HDD only

recommended

Power Supply

920W Redundant Power Supplies Platinum Level (94%)

Cooling System

3x 80mm 7K RPM Chassis middle fan w/ housing

Form Factor

Form Factor 2U Rackmount

Height 3.5" (89mm), : Width 17.2" (437 mm), Depth 25.5" (648mm)

Email: info@tyronesystems.com

For more/current product information, visit www.tyronesystems.com

O Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of intel Corporation in the U.S and/Or other Countries