## **Tyrone Camarero Specifications**

# **Tyrone**

### Camarero DS3007R-216R4

#### **Key features**

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 Express chipset
- Up to 3TB ECC 3DS LRDIMM, up to DDR4- 2400 MHz; 24x DIMM slots
- 2x PCI-E 3.0 x16, 3x PCI-E 3.0 x8, and 1x PCI-E 2.0 x4 (in x8) slot
- 8x 2.5" SAS3 and 8x 2.5" SATA3 Hot-swap Drive Bays
- Quad GbE ports w/ Intel i350
- I/O ports: 2x SuperDOM, 1x VGA, 2x COM, 2x USB 3.0 (rear), 4x USB 2.0 (2 rear, 2 front), 1x Type A
- 3x 8cm high-performance PWM fans
- 920W Redundant Power Supplies Platinum Level (94%)







#### Processor/Cache

Processor Dual socket R3 (LGA 2011) supports Intel®

Xeon® processor E5-2600v4/ v3 family

#### Chipset

Chipset Intel® C612 Express chipset

#### **System Memory**

Memory Capacity 24x 288-pin DDR4 DIMM slots, Up to 3TB

ECC 3DS LRDIMM, 768GB ECC RDIMM

#### **Expansion Slots**

PCI-Express 2x PCI-E 3.0 x16 3x PCI-E 3.0 x8

1x PCI-E 2.0 x4 (in x8)

#### **Integrated On-Board**

SAS LSI 3108 SAS3 (12Gbps) controller; HW

RAID 0, 1, 5, 6, 10, 50, 60

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 4x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port

#### **Add-on Options**

Optical Drive Optional

#### **Front Panel**

LED Indicators Power LED, Hard drive activity LED,

2x Network activity LEDs,System
Overheat LED / Fan fail LED / UID LED

Buttons Power On/Off button, System Reset button

#### **Drive Bays**

HDD bays 8x 2.5" and 8x 2.5" Hot-swap drive bays

#### **Power Supply**

920W Redundant Power Supplies Platinum Level (94%)

#### **Cooling System**

3x 8cm heavy duty fans with optimal fan speed control

#### **Form Factor**

Form Factor 2U Rackmount

Width: 17.2" (437 mm), Height: 3.5" (89mm) , Depth: 24.8" (630mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com