

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS3007R-416R

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 Express chipset
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 16x DIMM slots
- 1x PCI-E 3.0 x16, 6x PCI-E 3.0 x8 slot
- Intel® i350 Dual port GbE LAN
- I/O ports: 2x SuperDOM, 1x VGA, 2x COM, 2x USB 3.0, 4x USB 2.0
- 8x 3.5" Hot-swap SATA3 HDD Bays;8x 2.5" Hot-swap SAS3 drives in mobile rack; 1x 5.25" drive bay
- 3x 8cm Hot-swap redundant PWM Cooling Fans 2x 8cm Hot-swap Rear Exhaust PWM Fans & air shroud
- 920W Redundant Power Supplies Platinum Level (94%)
- Tower or Rackmount



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LED Indicators	Power LED Hard drive activity LED , 2x Network activity LEDs , System Overheat LED Power Fail LED
Buttons		Buttons	Power On/Off button System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 Express chipset	HDD bays	8x 3.5" Hot-swap SATA3 drive trays 8x 2.5" Hot-swap SAS3 drives in mobile rack
		Peripheral Bays	1x 5.25" drive bay (optional devices)
System Memory		Power Supply	
Memory Capacity	16x 288-pin DDR4 DIMM slots,Up to 2TB ECC 3DS LRDIMM, 512GB ECC RDIMM	920W Redundant Power Supplies Platinum Level (94%)	
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16, 6x PCI-E 3.0 x8 slot	3x 8cm Hot-swap redundant PWM Cooling Fans. 2x 8cm Hot-swap Rear Exhaust PWM Fans & air shroud	
Integrated On-Board		Form Factor	
SAS	LSI 3108 SAS3 (12Gbps) controller; HW RAID 0, 1, 5, 6, 10, 50, 60	Form Factor	4U Rackmountable / Tower
SATA LAN	SATA3 (6Gbps); RAID 0, 1, 5, 10 2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		Width: 7.0" (178 mm), Height: 17.2" (437mm) , Depth: 25.5" (648mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Optical Drive	Optional		

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other Countries
 © Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners