

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS3007R-416RT

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 16x DIMM slots
- 1x PCI-E 3.0 x16, 6x PCI-E 3.0 x8 slot
- Intel® X540 Dual port 10GBase-T
- I/O ports: 2x SuperDOM, 1x VGA, 2x COM, 2x USB 3.0, 4x USB 2.0
- 8x 3.5" Hot-swap SATA3 HDD Bays;8x 2.5" Hot-swap SAS3 drives in mobile rack; 1x 5.25" drive bay
- 3x 8cm Hot-swap redundant PWM Cooling Fans. 2x 8cm Hot-swap Rear Exhaust PWM Fans & air shroud
- 920W Redundant Power Supplies Platinum Level (94%)
- Tower or Rackmount



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LED Indicators	Power status LED, Hard drive activity LED, 2x Network activity LEDs, System Information LED, Power Fail LED
Buttons		Buttons	Power On/Off button System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD bays	8x 3.5" Hot-swap SATA3 drive trays. 8X 2.5" Hot-swap SAS3 drives in mobile rack.
System Memory		Power Supply	
Memory Capacity	16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 512GB ECC RDIMM	920W Redundant Power Supplies Platinum Level (94%)	
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x16, 6x PCI-E 3.0 x8 slot	3x 8cm Hot-swap redundant PWM Cooling Fans. 2x 8cm Hot-swap Rear Exhaust PWM Fans & air shroud	
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Form Factor	4U Rackmountable/Tower
SAS	LSI 3108 SAS3 (12Gbps) controller; HW RAID 0, 1, 5, 6, 10, 50, 60	Height	: 7.0" (178 mm),
LAN	2x RJ45 10GBase-T ports. 1x RJ45 Dedicated IPMI LAN port	Width	: 17.2" (437 mm),
		Depth	: 25.5" (648 mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Optical Drive	Optional		