

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TG-14RT

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v3 family; QPI up to 9.6GT/s
- Up to 1TB ECC, up to DDR4 2133MHz; 16x DIMM sockets
- 4x PCI-E 3.0 x16 slots (3x GPU/MIC cards optional), 1x PCI-E 3.0 x8 LP slot
- Intel X540 Dual port 10GBase-T
- 4x Hot-swap 2.5" SATA3 Drive Bays
- 1600W Redundant Power Supplies Platinum Level (94%+)
- 10x Counter rotating fans w/ optimal fan speed control
- Smart server management tools



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v3 family; QPI up to 9.6GT/s	LED Indicators	Power LED Hard drive activity LED , 2x Network activity LEDs ,System Overheat LED / Fan fail LED / UID LED
		Buttons	Power On/Off button System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 Express chipset	HDD bays	4x 2.5" Hot-swap drive bays
System Memory		Power Supply	
Memory Capacity	16x 288-pin DDR4 DIMM sockets Up to 1TB ECC LRDIMM, 512GB ECC RDIMM	1600W Redundant Power Supplies Platinum Level (94%+)	
Expansion Slots		Cooling System	
PCI-Express	4x PCI-E 3.0 x16 slots (3x GPU/Xeon Phi cards optional) 1x PCI-E 3.0 x8 (in x16) low-profile slot	10x counter-rotating fans with optimal fan speed control	
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10	Form Factor	1U Rackmount
LAN	2x RJ45 10GBase-T ports 1x RJ45 Dedicated IPMI LAN port		Width- 17.2" (437mm) , Height-1.7" (43mm), Depth-30.6" (777mm)
Add-on Options		Email : info@tyronesystems.com	
Raid	Optional	For more/current product information, visit	
Optical Drive	None	www.tyronesystems.com	

○ Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries.
○ Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners.