Tyrone Camarero Specifications

Camarero DS300TN-110RT

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM, up to DDR4- 2400 MHz; 16x DIMM slots
- 2x PCI-E 3.0 x16 (FHHL) slots
- 10x Hot-swap 2.5" SAS/SATA HDD bays; 2x NVMe support
- Intel® X540 Dual port 10GBase-T LAN
- I/O ports: 2x SuperDOM, 1x VGA, 1x COM, 2x USB 3.0 (front), 4x USB 2.0 (rear)
- 2x SuperDOM (Disk on Module) ports
- 700W Redundant Power Supplies Platinum Level High-efficiency









Р	ro	CE	225	or/	'Ca	C	he

Processor Dual socket R3 (LGA 2011) supports Intel®

Xeon® processor E5-2600v4/ v3 family

Chipset

Chipset Intel® C612 chipset

System Memory

Memory Capacity 16x 288-pin DDR4 DIMM slots,Up to 2TB

ECC 3DS LRDIMM, 512GB ECC RDIMM

Expansion Slots

PCI-Express 2x PCI-E 3.0 x16 full-height, half-length

slots

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 2x RJ45 10GBase-T ports, 1x RJ45

Dedicated IPMI LAN port

Add-on Options

Raid Optional

Optical Drive None

Front Panel

LED Indicators Power status LED HDD activity LED ,

2x Network activity LEDs Universal

Information (UID) LED

Buttons Power On/Off button UID button

Drive Bays

Hotswap 8 SATA3 (6Gbps) ports and 2x NVMe/STAT3

hybrid ports (connected to onboard storage

controller)

Power Supply

700W Redundant Power Supplies Platinum Level High-efficiency

Form Factor

Form Factor 1U Rackmountable

 Width
 17.2" (437mm),

 Height
 1.7" (43mm),

 Depth
 23.5" (597mm)

Email: info@tyronesystems.com For more/current product information, visit

www.tyronesystems.com