

Tyrone Camarero Specifications

Tyrone®

Camarero DS300TQ-210R

Key features



Up to 4 GPU

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel®C612 chipset
- Up to 2 TB ECC 3DS LRDIMM , up to DDR4- 2400MHz ; 16 DIMM slots
- 4 PCI-E 3.0 x16 slots (GPU/MIC, opt.), 1 PCI-E 3.0 x8 (in x16) low-profile slot
- Intel® i350 Dual-Port GbE LAN
- 10 Hot-swap 2.5" SATA Drive Bays
- 5 heavy duty cooling fans
- Smart server management tools
- 2000W Redundant Power Supplies Platinum Level (94%+)

Processor/Cache

Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
-----------	--

Chipset

Chipset	Intel®C612 chipset
---------	--------------------

System Memory

Memory Capacity	16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 1TB ECC RDIMM
-----------------	--

Expansion Slots

PCI-Express	4 PCI-E 3.0 x16 slots (GPU/MIC, opt.), 1 PCI-E 3.0 x8 (in x16) low-profile slot
-------------	---

Integrated On-Board

SATA	Intel C612 Controller SATA3 (6Gbps) with RAID 0, 1, 5, 10
LAN	2 RJ45 Gigabit Ethernet LAN ports, 1 RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Card	Optional
Optical Drive	None

Front Panel

LED Indicators	Power LED, Hard drive activity LED, 2 Network activity LEDs, System Overheat LED / Fan fail LED /UID LED
Buttons	Power On/Off button , System Reset button

Drive Bays

HDD Bays	10 Hot-swap 2.5" drive bays
----------	-----------------------------

Power Supply

2000W Redundant Power Supplies Platinum Level (94%+)
--

Cooling System

5 heavy duty 8cm fans with optimal fan speed control
--

Form Factor

Form Factor	2U Rackmount
Height	: 3.5" (89mm),
Width	: 17.2" (437 mm),
Depth	: 31" (787mm)

Email : info@tyronesystems.com

**For more/current product information, visit
www.tyronesystems.com**