

Tyrone Camarero Specifications



Camarero DS300TR-14R

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Up to 1TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 8x DIMM slots
- 1x PCI-E 3.0 x8 FHHL Expansion slot
- Intel® i210 Dual port Gigabit Ethernet
- IPMI 2.0 + KVM with Dedicated LAN
- 4x 3.5" Hot-swap SATA3 HDD Bays
- I/O ports: 2x SuperDOM, 1x VGA, 1x COM, 2x USB 3.0, 2x USB 2.0
- 400W Redundant Power Supplies Gold Level Certified



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LEDs	Power status LED HDD activity LED , 2x Network activity LEDs Universal Information (UID) LED
		Buttons	Power On/Off button System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 Express chipset	HDD bays	4x 3.5" Hot-swap SATA HDD trays
System Memory		Power Supply	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, 256GB ECC RDIMM		400W Redundant Power Supplies Gold Level Certified
Expansion Slots		Cooling System	
PCI-Express	1x PCI-E 3.0 x8 Full-height Half-length		4x 4cm 17.5K RPM PWM fans
Integrated On-Board		Form Factor	
SATA	I-SATA 4 & I-SATA 5 support SATA DOM SATA3 (6Gbps); RAID 0, 1, 5, 10		1U Rackmount
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port	Dimension	Width-17.2" (437mm) , Height-1.7" (43mm), Depth-19.8" (503mm)
Add-on Options		Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com	
Raid	Optional		
Optical Drive	Optional		

○ Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/or other Countries
 ○ Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks .All other brands and names are the property of their respective owners