

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TR-14RT

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family QPI up to 9.6GT/s
- Intel® C612 chipset
- Up to 1TB ECC 3DS LRDIMM, up to DDR4- 2400MHz ; 8x DIMM slots
- 1x PCI-E 3.0 x8 (FHHL) slot)
- 4x 3.5" Hot-swap SATA3 Drive Bays
- Intel® 82599ES Dual-Port 10GbE LAN with SFP+
- I/O ports: 1x VGA, 1x COM, 4x USB 2.0
- 500W Redundant High-Efficiency Power Supplies Platinum Level Certified
- 2x SuperDOM (Disk on Module) ports
- IPMI 2.0 + KVM with Dedicated LAN



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600 v4/ v3 family	LED Indicators	Power status LED ,HDD activity LED, 2x Network activity LEDs,Universal Information (UID) LED
		Buttons	Power On/Off button System Reset button
Chipset		Drive Bays	
Chipset	Intel® C612 chipset	HDD Bays	4x 3.5" Hot-swap SATA3 Drive Bays
		Peripheral Drives	1x Slim DVD-ROM drive (optional)
System Memory		Power Supply	
Memory Capacity	8x 288-pin DDR4 DIMM slots, Up to 1TB ECC 3DS LRDIMM, 256 ECC RDIMM		500W Redundant High-Efficiency Power Supplies Platinum Level Certified
Expansion Slots		Cooling System	
	1x PCI-E 3.0 x8 (FHHL) slot		5x 4cm fans with optimal fan speed control
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Form Factor	1U Rackmount
LAN	2x 10 Gigabit Ethernet SFP+ ports, 1x RJ45 Dedicated IPMI LAN port	Width:	17.2" (437mm),
		Height:	1.7" (43mm),
		Depth:	25.6" (650mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	Optional		