Tyrone Camarero Specifications

vrone

Camarero DS300TR-28RT4

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 Express chipset
- Up to 3TB ECC 3DS LRDIMM, up to DDR4- 2400 MHz; 24x DIMM slots
- 2 PCI-E 3.0 x16, 3 PCI-E 3.0 x8, and 1 PCI-E 2.0 x4 (in x8) slot
- Quad LAN w/ Intel® X540 10GBase-T
- 10x SATA3 (6Gbps); RAID 0, 1, 5, 10
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 3x USB 3.0 (2 rear, 1 Type A)
- 8x 3.5" Hot-swap SAS / SATA Drive
- 2x Fixed 3.5" Drive Bays
- 3x 80x38mm 4-pin PWM Fans
- 740W Redundant Power Supplies Platinum Level (94%)







Processor/Cache

Processor Dual socket R3 (LGA 2011) supports Intel®

Xeon® processor E5-2600v4/ v3 family

Chipset

Intel® C612 Express chipset Chipset

System Memory

Memory Capacity 24x 288-pin DDR4 DIMM slots, Up to 3TB

ECC 3DS LRDIMM, 768GB ECC RDIMM

Expansion Slots

PCI-Express 2 PCI-E 3.0 x16, 3 PCI-E 3.0 x8, and

1 PCI-E 2.0 x4 (in x8) slot

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 4x RJ45 10GBase-T ports 1x RJ45

Dedicated IPMI LAN port

Add-on Options

Raid Optional

Optical Drive Optional **Front Panel**

LED Indicators Power LED Hard drive activity LED

2x Network activity LEDs System Overheat

LED Power fail LED

Buttons Power On/Off button System Reset button

Drive Bays

HDD bays 8x 3.5" Hot-swap SAS / SATA Drive Bays.

2X Fixed 3.5" Drive Bays

Slim DVD-ROM drive (Optional) Peripheral Bays

Power Supply

740W Redundant Power Supplies Platinum Level (94%)

Cooling System

3x 80x38mm 4-pin PWM Fans

Form Factor

Form Factor 2U Rackmountable

> Width: 17.2" (437 mm), Height: 3.5" (89mm), Depth: 25.5" (648mm)

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com