# **Tyrone Camarero Specifications**

# Ivrone

## Camarero DS300TR-424R4

#### **Key features**

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 familyS
- Up to 3TB ECC 3DS LRDIMM, up to DDR4- 2400 MHz; 24x DIMM slots
- 2 PCI-E 3.0 x16, 3 PCI-E 3.0 x8, and 1 PCI-E 2.0 x4 (in x8) slot
- Quad LAN w/ Intel® i350 GbE
- 10x SATA3 (6Gbps); RAID 0, 1, 5, 10
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 3x USB 3.0 (2 rear, 1 Type A)
- 24x 3.5" hot-swap SAS/SATA drive bays supporting SAS3/2 or SATA3 HDDs with 12Gbps throughput
- Optimized chassis cooling with redundant cooling fans and adjustable air shroud
- E1C: Single SAS3 (12Gbps) expander backplane; E2C: Dual SAS3 (12Gbps) expanders backplane
- Mini SAS HD (SFF 8643) connectivity on backplane
- Can be configured as "JBOD or Headunit"
- Redundant 1280W Platinum Level power supply







#### Processor/Cache

Processor Dual socket R3 (LGA 2011) supports Intel®

Xeon® processor E5-2600v4/v3 family

#### Chipset

Intel® C612 chipset Chipset

#### **System Memory**

**Memory Capacity** 24x 288-pin DDR4 DIMM slots, Up to 3TB

ECC 3DS LRDIMM, 768GB ECC RDIMM

#### **Expansion Slots**

**PCI-Express** 2 PCI-E 3.0 x16, 3 PCI-E 3.0 x8,

1 PCI-E 2.0 x4 (in x8)

#### **Integrated On-Board**

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 4x RJ45 Gigabit Ethernet LAN ports,

1x RJ45 Dedicated IPMI LAN port

### **Add-on Options**

Raid Optional

**Optical Drive** None

#### **Front Panel**

**LED Indicators** 2 Network Activity LEDs Fan Fail/System

> Over Heat LED HDD activity LED Power Status LED Unit Identification (UID) LED

**Buttons** Power On/Off button System Reset Button

#### **Drive Bays**

HDD bays 24 3.5" hot-swap drive bay SAS or

enterprise SATA HDD only recommended

Peripheral Bays Optional 2 x 2.5" hot-swap drive bay,

> Optional 1 x 3.5" internal fixed drive bay, Optional 2 x 2.5" internal fixed drive bay

#### **Power Supply**

Redundant 1280W Platinum Level power supply

#### **Cooling System**

3x 8cm hot-swap redundant PWM cooling fans, 2x 80mm rear hot-swap exhaust PWM fan

#### **Form Factor**

Form Factor **4U Rackmountable** 

> Width- 17.2" (437mm), Height- 7" (178mm), Depth - 26.5" (673mm)

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com