Tyrone Camarero Specifications

Camarero DS300TR-48

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 Express chipset
- Up to 2TB ECC 3DS LRDIMM, up to DDR4- 2400 MHz; 16x DIMM slots
- 3x PCI-E 3.0 x16, 2x PCI-E 3.0 x8, and 1x PCI-E 2.0 x4 (in x8) slot supports Thunderbolt 2.0 AIC
- Intel® i210 Dual port GbE LAN
- 7.1 HD Audio
- 8x 3.5" Hot-swap SATA HDD Bays
- 2x 2800 RPM Fans 1x 2700 RPM Fan
- 1200W High Efficiency Power Supply Platinum Level (94%)
- Tower or Rackmount







Processor/Cache

Processor Dual socket R3 (LGA 2011) supports Intel®

Xeon® processor E5-2600v4/v3 family

Chipset

Intel® C612 Express chipset Chipset

System Memory

Memory Capacity 16x 288-pin DDR4 DIMM slots,Up to 2TB

ECC 3DS LRDIMM, 512GB ECC RDIMM

Expansion Slots

PCI-Express 3x PCI-E 3.0 x16, 2x PCI-E 3.0 x8, and

1x PCI-E 2.0 x4 (in x8) slot supports

Thunderbolt 2.0 AIC

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 2x RJ45 Gigabit Ethernet LAN ports

Add-on Options

Raid Optional

Optical Drive Optional

Front Panel

LED Indicators Power status LED Hard drive activity

LED 2x Network activity LEDs System

Overheat LED Fan fail LED

Buttons Power On/Off button System Reset button

Drive Bays

HDD bays 8x 3.5" Hot-swap SAS/SATA Drive Trays

Peripheral Bays 3x 5.25" Drive Bays

Power Supply

1200W High Efficiency Power Supply Platinum Level (94%)

Cooling System

2x 2800 RPM Fans 1x 2700 RPM Fan

Form Factor

Form Factor 4U Rackmountable/Tower

> Width: 7.0" (178 mm), Height: 17.8" (452mm), Depth: 25.5" (648mm)

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com