

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TU-224R4

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 Express chipset
- Up to 3TB ECC 3DS LRDIMM, up to DDR4- 2400MHz; 24x DIMM slots
- 1x PCI-E 3.0 x16 slot (FH, 10.5" L), 7x PCI-E 3.0 x8 slots (5x FH, 10.5" L, 1x LP, 1x Internal LP)
- 4x Gigabit Ethernet ports
- 24x Hot-swap 2.5" Drive Bays: 10x SATA3 ports by default; Optional drive support: 24x SAS3
- 4x heavy duty fans w/ optimal fan speed control
- 1000W High efficiency (96%) Redundant PSU; Titanium Level



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LEDs	Power status LED,HDD activity LED, 2x Network activity LEDs,System information (overheat/UID) LED
Chipset	Intel® C612 Express chipset	Buttons	Power On/Off button,System Reset button
System Memory		Drive Bays	
Memory Capacity	24x 288-pin DDR4 DIMM slots, Up to 1.5TB ECC LRDIMM, RDIMM	HDD Bays	24x Hot-swap 2.5" Drive Bays:10x SATA3 ports by default Optional drive support: 24x SAS3
Expansion Slots		Power Supply	
PCI-Express	1x PCI-E 3.0 x16 slot (FH, 10.5" L) 7x PCI-E 3.0 x8 slots (5x FH, 10.5" L, 1x LP, 1x Internal LP)		1000W High efficiency (96%) Redundant PSU; Titanium Level
Integrated On-Board		Cooling System	
SATA	SATA3 (6Gbps) with RAID 0, 1, 5, 10		4x 8cm heavy duty PWM fans
LAN	4x Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port	Form Factor	
Add-on Options		Form Factor	2U Rackmount
Raid	Optional	Width:	17.2" (437 mm),
Optical Drive	None	Height:	3.5" (89mm)
		Depth:	27.76" (705.3mm)
		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	