

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TW-110R

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 16x DIMM slots
- 2x PCI-E 3.0 x16 (FHHL), 1x PCI-E 3.0 x8 Mezzanine for HBA cards
- 10x Hot-swap 2.5" SAS/SATA HDD bays
- Intel® i350 Dual port GbE LAN
- I/O ports: 2x SuperDOM, 1x VGA, 1x COM, 6x USB 3.0 (4 rear, 2 front)
- 2x SuperDOM (Disk on Module) ports
- 700W Redundant Power Supplies Platinum Level High-efficiency



Processor/Cache		Front Panel	
Processor	Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family	LED Indicators	Power status LED HDD activity LED 2x Network activity LEDs Universal Information (UID) LED
		Buttons	Power On/Off button UID button
Chipset		Drive Bays	
Chipset	Intel® C612 Express chipset	HDD bays	10x Hot-swap 2.5" SAS / SATA HDD trays (connected to onboard storage controller)
System Memory		Power Supply	
Memory Capacity	16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 512GB ECC RDIMM		700W Redundant Power Supplies Platinum Level High-efficiency
Expansion Slots		Cooling System	
PCI-Express	2x PCI-E 3.0 x16 full-height, Half-length slots		5x 4cm heavy-duty counter-rotating fans w/ air shroud and optimal fan speed control
Integrated On-Board		Form Factor	
SATA	SATA3 (6Gbps); RAID 0, 1, 5, 10	Form Factor	1U Rackmountable
LAN	2x RJ45 Gigabit Ethernet LAN ports 1x RJ45 Dedicated IPMI LAN port		Width 17.2" (437mm) , Height 1.7" (43mm) , Depth 23.5" (597mm)
Add-on Options		<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	
Raid	Optional		
Optical Drive	None		