

Tyrone Camarero Specifications

Tyrone[®]

Camarero DS300TX-38R

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family
- Intel® C612 chipset
- Up to 2TB ECC 3DS LRDIMM , up to DDR4- 2400 MHz ; 16x DIMM slots
- 10x PCI-E 3.0 x8 (FHFL) slots, 1x PCI-E 2.0 x4 (in x8) slot
- Intel® i350 Dual port Gigabit Ethernet
- 8x 3.5" Hot-swap drive bays, 2x 5.25" drive bays
- Server remote management: IPMI 2.0 / KVM over LAN / Media over LAN
- 3x middle fans & 1x rear exhaust fan
- 980W Redundant Power Supplies Platinum Level (94%)



| Processor/Cache | | Front Panel | |
|---------------------|---|--|---|
| Processor | Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/v3 family | LED Indicators | Power status LED,Hard drive activity LED, 2x Network activity LEDs, System information (overheat/UID) LED, Power fail LED |
| | | Buttons | Power On/Off Button,System Reset Button |
| Chipset | | Drive Bays | |
| Chipset | Intel® C612 chipset | HDD bays | 8x 3.5" Hot-swap drive bays, 2x 5.25" drive bays |
| | | Peripheral Bays | 1x slim DVD-ROM drive (optional) |
| System Memory | | Power Supply | |
| Memory Capacity | 16x 288-pin DDR4 DIMM slots, Up to 2TB ECC 3DS LRDIMM, 512 ECC RDIMM | 980W Redundant Power Supplies Platinum Level (94%) | |
| Expansion Slots | | Cooling System | |
| PCI-Express | 10x PCI-E 3.0 x8 slots, 1x PCI-E 2.0 x4 (in x8) slot | 3x 8cm 7K RPM, Middle fans, 1x 8cm 6.7K RPM, Rear Exhaust fan | |
| Integrated On-Board | | Form Factor | |
| SATA | SATA3 (6Gbps) with RAID 0, 1, 5, 10 | Form Factor | 3U Rackmount |
| LAN | 2x RJ45 Gigabit Ethernet LAN ports, 1x RJ45 Dedicated IPMI LAN port | Height : | 5.2" (132mm), |
| | | Width : | 17.2" (437mm), |
| | | Depth : | 25.5" (648mm) |
| Add-on Options | | Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com | |
| Raid | Optional | | |
| Optical Drive | Optional | | |