Tyrone Camarero Specifications

Camarero DS301TR-26

Key features

- Dual socket R3 (LGA 2011) supports Intel® Xeon® processor E5-2600v4/ v3 family
- Intel® C612 chipset
- Up to 1TB ECC 3DS LRDIMM, up to DDR4- 2400MHz; 8x DIMM slots
- 3 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8), 1 PCI-E 3.0 x16, 1 PCI-E 2.0 x4 (in x8)
- Intel® i210 GbE LAN, 2 ports
- Integrated IPMI 2.0 and KVM with Dedicated LAN
- 6x 3.5" Hot-swap SAS / SATA Drive Bays
- 4x 80mm 6300 RPM Fans
- 650W High-efficiency Power Supply Gold Level Certified





P	ro	C	ess	or/	'Ca	C	h	e
---	----	---	-----	-----	-----	---	---	---

Processor Dual socket R3 (LGA 2011) supports Intel®

Xeon® processor E5-2600v4/ v3 family

Chipset

Intel® C612 chipset Chipset

System Memory

Memory Capacity 8x 288-pin DDR4 DIMM slots, Up to 1TB

ECC 3DS LRDIMM, 512GB ECC RDIMM

Expansion Slots

PCI-Express 3 PCI-E 3.0 x8, 1 PCI-E 3.0 x4 (in x8),

1 PCI-E 3.0 x16, 1 PCI-E 2.0 x4 (in x8)

Integrated On-Board

SATA I-SATA 4 and I-SATA 5 support SATA DOM

SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 2x RJ45 Gigabit Ethernet LAN ports,

1x RJ45 Dedicated IPMI LAN port

Add-on Options

Raid Optional

Optical Drive Optional **Front Panel**

LED Indicators Power LED Hard drive activity LED,

2x Network activity LEDs ,System Overheat

Buttons Power On/Off button System Reset button

Drive Bays

HDD bays 6x 3.5" SAS / SATA Hot-swap drive trays SAS

or enterprise SATA HDD only recommended

Peripheral Bays 1x 5.25" full-height Peripheral Drive Bay

Power Supply

650W High-efficiency Power Supply Gold Level Certified

Cooling System

4x 80mm 6300 RPM Fans

Form Factor

Form Factor 2U Rack mount

> Height 3.5" (89mm), Width 16.8" (426mm), Depth 25.6" (650mm)

Email: info@tyronesystems.com For more/current product information, visit www.tyronesystems.com