

Tyrone Camarero Specifications



Camarero DS4007E1-224RT

Key features

- **Corporate Database, Database Processing & Storage, Enterprise Server, HPC, Data Center, iSCSI SAN**
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 24 Hot-swap 3.5" SAS3/SATA3 drive bays; 2 hot-swap 2.5" SATA3 drive bays (rear), Expander based backplane
- 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x8, 1 SIOM card support (flexible networking), Note: must bundle with Network card
- Broadcom 3108 SAS3, HW RAID
- Server remote management: IPMI 2.0/ KVM over LAN / Media over LAN
- 5x 8cm high-performance PWM fans
- 1600W Redundant Power Supplies Titanium Level (96%)



Processor/Cache	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 3 UPI up to 10.4 GT/s
Chipset	
Chipset	Intel® C621 chipset
System Memory	
Memory Capacity	Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots; Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
Expansion Slots	
PCI-Express	2 PCI-E 3.0 x16 slots, 1 PCI-E 3.0 x8 slot, 1 SIOM card support, (must bundle with network card)
Integrated On-Board	
SAS	SAS 3 (12Gbps) via Broadcom 3108; HW RAID, RAID 0, 1, 5, 6, 10, 50, 60
SATA	SATA 3 (6Gbps); RAID 0, 1, 5, 10
LAN	1 RJ45 Dedicated IPMI LAN port
Add-on Options	
Optical Drive	None

Front Panel	
LED Indicators	Power status LED, Hard drive activity LED, Network activity LEDs, System Information LED, Power fail LED
Buttons	Power On/Off button, System Reset button
Drive Bays	
HDD Bays	24 Hot-swap 3.5" SAS3/SATA3 drive bays, 2 Hot-swap 2.5" SATA3 drive bays (rear)
Power Supply	
1600W Redundant Power Supplies Titanium Level (96%)	
Cooling System	
5x 8cm high-performance PWM fans	
Form Factor	
Form Factor	2U Rackmount
Height :	3.5" (89 mm),
Width :	17.2" (437 mm),
Depth :	34" (863 mm)
<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit</p> <p>www.tyronesystems.com</p>	