Tyrone Camarero Specifications

Camarero DS4007TP-224R

Key features

Compute Intensive Application, HPC, Data Center, Enterprise Server, Financial Analysis, Mission-critical applications Four hot-pluggable systems (nodes) in a 2U form factor, Each node supports the following:

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors.Dual Socket P (LGA 3647) supported, CPU TDP support 165W TDP, 2 UPI up to 10.4 GT/s
- Intel [©]C621 chipset
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots;Up to 2TB Intel[®] Optane[™] DC Persistent Memory in memory mode (Cascade Lake only)
- 2 PCI-E 3.0 x16 slots
- Flexible Networking support via SIOM; Dedicated IPMI 2.0 LAN
- 6 Hot-swap 2.5" SAS/SATA drive bays
- Broadcom 3108 SAS3 controller; RAID 0, 1, 5, 6, 10, 50 w/ SuperCap opt.
- 2200W Redundant Power Supplies Titanium Level (96%)

Processor/Cache 2nd Generation Intel® Xeon® Scalable Processor Processors (Cascade Lake-SP), Intel® Xeon[®] Scalable Processors.Dual Socket P (LGA 3647) supported, CPU TDP support 165W TDP, 2 UPI up to 10.4 GT/s Chipset Chipset Intel ®C621 chipset System Memory Memory Capacity Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots;Up to 2TB Intel[®] Optane[™] DC Persistent Memory in memory mode (Cascade Lake only) **Expansion Slots PCI-Express** 2 PCI-E 3.0 x16 slots Integrated On-Board SAS Broadcom 3108 SAS3 (12Gbps) controller; RAID 0, 1, 5, 6, 10, 50 support. **Optional SuperCap** LAN 1 RJ45 Dedicated IPMI LAN port Add-on Options

Optical Drive

None

lyrone





Front	Panel	
-------	-------	--

LED Indic	ators	Power status LED, HDD activity LED, Network activity LEDs, Universal Information (UID) LED
Buttons		Power On/Off button, UID button
Drive Bay	S	
HDD Bay	5	6 Hot-swap 2.5" SAS/SATA HDD trays
Power Suj	pply	
2200W Re	dundant	Power Supplies Titanium Level (96%)
Cooling S	ystem	
4 Heavy d	uty 8cm	PWM fans with optimal fan speed control
Form Fact	or	
Form Fact	or	2U Rackmount
Torritaci		
Height Width	:	3.47" (88mm), 17.25* (438mm),

Email : info@tyronesystems.com For more/current product information, visit www.tyronesystems.com

o Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S and/Or other Countries

D Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners