

Tyrone Camarero Specifications

Tyrone

Camarero DS400TR-54R

Key features

- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621
- Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots;Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 4 PCI-E 3.0 x16,2 PCI-E 3.0 x8,M.2 Interface: PCI-E 3.0 x4,M.2 Form Factor: 2260, 2280, 22110,M.2 Key: M-Key,2 PCI-E 3.0 NVMe x4 Internal Port(s)
- 1 VGA port
- Dual LAN with GbE from C621
- External:5.25" x 4, 3.5" x 1,Internal: 3.5" or 2.5" x 5
- Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10
- 550/1200 Redundant Power Supply, 80 Plus platinum
- Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan



Processor/Cache		Front Panel	
Processor	2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors. Dual Socket P (LGA 3647) supported, CPU TDP support 205W, 2 UPI up to 10.4 GT/s	Front Panel	Front Control Panel Power Switch, System Reset
Chipset		Buttons	Power On/Off button
Chipset	Intel® C621	Drive Bays	
System Memory		HDD Bays	External:5.25" x 4, 3.5" x 1, Internal: 3.5" or 2.5" x 5
Memory Capacity	Up to 4TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 4TB 3DS ECC LRDIMM, DDR4-2933MHz, in 16 DIMM slots;Up to 2TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).	Power Supply	
Expansion Slots		550/1200 Redundant Power Supply, 80 Plus platinum	
PCI-Express	4 PCI-E 3.0 x16,2 PCI-E 3.0 x8,M.2 Interface: PCI-E 3.0 x4,M.2 Form Factor: 2260, 2280, 22110,M.2 Key: M-Key,2 PCI-E 3.0 NVMe x4 Internal Port(s)	Cooling System	
Integrated On-Board		Front:120 x 25 mm x1 PWM Fan, Rear: 120 x 25 mm x1 PWM Fan	
SATA	Intel® C621 controller for 10 SATA3 (6 Gbps) ports; RAID 0,1,5,10	Form Factor	
LAN	Dual LAN with GbE from C621	Form Factor	Tower/Convertible/ Rackmount
Add-on Options		Dimensions	: 560 x 200 x 430 mm (22" x 7.9" x 16.9")
Raid Card	Optional	<p>Email : info@tyronesystems.com</p> <p>For more/current product information, visit www.tyronesystems.com</p>	
Optical Drive	None		

© Intel, the Intel logo, the Intel Inside logo, Xeon, and Intel Xeon Phi are trademarks of Intel Corporation in the U.S. and/or other countries. Specifications subject to change without notice. Picture used for representation purpose only and the actual product may differ in looks. All other brands and names are the property of their respective owners.