Tyrone Camarero Specifications

Camarero DS400TU-110RTP

Key features

- Virtualization, Cloud Computing, High End Enterprise Server
- 2nd Generation Intel® Xeon® Scalable Processors (Cascade Lake-SP), Intel® Xeon® Scalable Processors., Dual Socket P (LGA 3647) supported,
 CPU TDP support 205W, 2 UPI up to 10.4 GT/s
- Intel® C621 chipset
- Up to 6TB 3DS ECC RDIMM, DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode (Cascade Lake only).
- 2 PCI-E 3.0 x16 slots (FH, 10.5" L), 2 PCI-E 3.0 x8 slots (1 LP, 1 internal LP)
- 2 10G SFP+ Ethernet ports
- 10 Hot-swap 2.5" Drive Bays; 10 SATA3 (2 hybrid ports 2 NVMe opt.);
 Optional M.2 NVMe and SATA3 ports
- 8 heavy duty fans w/ optimal fan speed control
- 750W Redundant Power Supplies Platinum Level (94%+)









Processor/Cache

Processor 2nd Generation Intel® Xeon® Scalable
Processors (Cascade Lake-SP), Intel®
Xeon® Scalable Processors., Dual Socket P

(LGA 3647) supported, CPU TDP support

205W, 2 UPI up to 10.4 GT/s

Chipset

Chipset Intel® C621 chipset

System Memory

Memory Capacity Up to 6TB 3DS ECC RDIMM,

DDR4-2933MHz; Up to 6TB 3DS ECC LRDIMM, DDR4-2933MHz, in 24 DIMM slots;Up to 6TB Intel® Optane™ DC Persistent Memory in memory mode

(Cascade Lake only).

Expansion Slots

PCI-Express 2 PCI-E 3.0 x16 slots (FH, 10.5" L),

2 PCI-E 3.0 x8 slots (1 LP, 1 internal LP)

Integrated On-Board

SATA SATA3 (6Gbps); RAID 0, 1, 5, 10

LAN 2 10G SFP+ ports,1 RJ45 Dedicated

IPMI LAN port

Add-on Options

Raid Card Optional
Optical Drive None

Front Panel

LED Indicators Power LED, Hard drive activity LED,

Network activity LEDs, System Overheat

LED / Fan fail LED /UID LED

Buttons Power On/Off button, System

Reset button

Drive Bays

HDD bays 10 Hot-swap 2.5" drive bays; 10 SATA3

(2 hybrid ports - 2 NVMe opt.)

M.2 1 M.2 NVMe and 1 M.2 SATA3 via optional

riser card RSC-UMR-8 and cable CBL-SAST-0538 (2240/2260/2280/22110), 2 M.2 NVMe via optional add-on card AOC-SLG3-

2M2 (2260/2280/22110)

Power Supply

750W Redundant Power Supplies Platinum Level (94%+)

Cooling System

8 heavy duty fans w/ optimal fan speed control

Form Factor

Form Factor 1U Rackmount
Height : 1.7" (43mm),
Width : 17.2" (437mm),
Depth : 28.5" (724mm)

Email: info@tyronesystems.com

For more/current product information, visit

www.tyronesystems.com