

Tyrone Camarero Specifications

Tyrone[®]

Camarero SS00TK-46R

Key features

- Single socket P (LGA 3647) supports Intel® Xeon® Phi™ x200 processor, CPU TDP support Up to 260W
- Intel® C612 chipset
- Up to 384GB ECC LRDIMM, 192GB ECC RDIMM, DDR4-2400MHz in 6 DIMM slots
- 2 PCI-E 3.0 x16, 1 PCI-E 3.0 x4
- 6x 3.5" and 4x 2.5" tool-less drive bays, 2x 5.25" peripheral bays
- Dual GbE LAN port via Intel® i350
- Dual cooling zones, 6 fans total 1x 12cm rear exhaust fan
- 750W Multi-output Power Supply



Processor/Cache

Processor	Single socket P (LGA 3647) supports Intel® Xeon® Phi™ x200 processor, CPU TDP support Up to 260W
-----------	--

Chipset

Chipset	Intel® C612 chipset
---------	---------------------

System Memory

Memory Capacity	6x 288-pin DDR4 DIMM slots , Up to 384GB Load Reduced ECC LRDIMM Up to 192GB ECC RDIMM
-----------------	--

Expansion Slots

PCI-Express	2 PCI-E 3.0 x16 slots,1 PCI-E 3.0 x4 slot
-------------	---

Integrated On-Board

SATA	SATA3 (6Gbps) via C612 controller RAID 0, 1, 5, 10 support
LAN	2 RJ45 Gigabit Ethernet LAN ports, 1 Dedicated IPMI LAN port

Add-on Options

Raid	Optional
Optical Drive	Optional

Front Panel

LED	Power LED,Hard drive activity LED
Buttons	Power On/Off button,Reset Button

Drive Bays

Internal HDD	6x 3.5" and 4x 2.5" tool-less drive bays
Peripheral	2x 5.25" Peripheral drive bays

Power Supply

750W Multi-output Power Supply

Cooling System

2x 12cm front chassis fans,1x 8cm mid chassis fan, 1x 12cm rear chassis fans,2x 12cm radiator exhaust fans. Closed loop Liquid Cooling unit.

Form Factor

Form Factor	Tower
Height	: 18.1" (460mm),
Width	: 7.9" (201mm),
Depth	: 19.4" (493mm)

Email : info@tyronesystems.com

For more/current product information, visit
www.tyronesystems.com